

Perforating, creasing & folding TOUCHLINE CP375 & TCF375

Stop perforation in both directions is one of the key features of the new TOUCHLINE CP375. And due to the interchangeable tools, the CP375 can be diverted from a perforating into a creasing machine or vice versa within no time. In conjunction with the online creasing and folding machine TOUCHLINE TCF375, the CP375 will be able to produce even more complex jobs online; stop perforation in both directions, creasing and folding all in one operation.



Technical specifications TOUCHLINE CP375 & TCF375

| | | | |
|---------------------------------|--|------------------------|--|
| Feeder system | pile feeder, top fed, vacuum belt | Double sheet detection | ultrasonic, optional |
| Feeder capacity | 100 mm | Working system | Multigraf Quick-Set interchangeable tools |
| Sheet transfer device | vacuum belt | Deliveries | folding = shingling delivery creasing only = lower reception tray |
| Paper size minimum | 105 x 148 mm | Speed | depending on job, up to 6000 A4/h |
| Paper size maximum | 375 x 660 mm 375 x 1050 mm with table extension | Dimension | 3150 x 600 x 1340 mm |
| Paper stocks creasing & folding | 80-400 gsm or max. 0.4 mm * | Weight | 309kg |
| Paper stocks perforating | 80-300 gsm or max. 0.3 mm * | Electrical connection | 100-240 VAC, 50/60 Hz |
| Control panel | touchscreen | | |

* Light stocks depending on paper quality.

Various online solutions are possible with the TOUCHLINE TCF375



KAS 50 in combination with the TOUCHLINE TCF375.



Duplo DC-615 online with the TOUCHLINE TCF375.

Sample applications TOUCHLINE CP375 & TCF375

